



W3-D6004



Specification:

Model No.	W3-D6004
Video Input	4 CH BNC
Video Output	BNC X 1, VGA X 1
Audio Input/Output	RCA 2-channel / 2-channel
Compression	H.264 (9 image quality optional)
Operation Mode	Hexaplex (record, display, playback, backup, operate, remote control)
Video Record Resolution	(PAL) Display:704x576 Playback:4CH(CIF) 352x288 Half D1:720 x 240 D1:720 x 480
	(NTSC) Display:720x480 Playback:4CH(CIF) 360x240 Half D1:720 x 288 D1:720 x 576
Frame Per Second	(PAL) Display:100fps Record:MAX.100 fps(Quad) Each: CIF:25fps/s(Real Time) Half D1:12.5fps/s D1:6.25fps/s
	(NTSC) Display: 120fps Record:MAX.120 fps(Quad) Each: CIF:30fps/s(Real Time) Half D1:15fps/s D1:7.5fps/s
Live Display	Real Time, Single, Quad
Video Adjustment	Brightness, Contrast, Color, Watermark
Alarm Input	4 CH
Alarm Output	1 CH
Recording Mode	Continuous, Motion Detection, Sensor, Time schedule
Playback Search	Time, Event(Motion, Alarm)
Motion Detention	Yes, with configurable detection area & sensitivity
Video Loss Alarm	Yes
Remote Controller	Yes
Network/IP	RJ45
Pan/Tilt/Zoom	RS485/RS-232
Restore Configuration after Power Outage	Auto
HDD storage	One IDE HDD
USB backup	USB 2.0 (Support external DVD-RW, removable HDD)
Power Supply	DC 12V/5A
Weight	8 KG
Dimension (L x W x H)	315 x 250 x 52mm
Operating Temperature	-20°C ~ +60°C