



W3-D6404CWM Integrated Standalone DVR with Built in LCD



Specification:

Model No.	W3-D6404CWM
Video Input	4 CH BNC
Video Output	BNC X 1
Audio Input/Output	RCA 1-channel / 1-channel
Compression	Video:H.264 Baseline Compression; Audio: G.726 8k*16bit ADPCM Mono
Operation Mode	Triplex(playback/record/network)
Video Record Resolution	(PAL) Display:704x576 Playback:4CH(CIF) 352x288
	(NTSC) Display:720x480 Playback:4CH(CIF) 360x240
Frame Per Second	(PAL) Display:100fps Record:MAX.100 fps(Quad) Each: CIF:25fps/s(Real Time)
	(NTSC) Display: 120fps Record:MAX.120 fps(Quad) Each: CIF:30fps/s(Real Time)
Live Display	Real Time, Single, Quad
Video Adjustment	Brightness, Contrast, Color
Alarm Input	4 CH
Alarm Output	1 CH
Recording Mode	Continuous, Motion Detection, Sensor, Time schedule
Playback Search	Time, Event(Motion, Alarm)
Motion Detention	Yes, with configurable detection area & sensitivity
Video Loss Alarm	Yes
Remote Controller	Yes
Network/IP	RJ45
Pan/Tilt/Zoom	RS485
Restore Configuration after Power Outage	Auto
HDD storage	One SATA HDD UP to 1TB
USB backup	1.USB 2.0 flash drive; 2. Network; 4.USB DVD-RW
Power Supply	DC 12V / 3A
Weight	5 KG
Dimension (L x W x H)	315(W) x 224(D) x 52(H) mm
Operating Temperature	-20°C ~ +60°C