




ACTO LX 640



Features and Specification:

 detailed specifications	
Display Type	0.63" Sony XGA LCD Panels
Resolution	Native XGA (1024 x 768)
Brightness (Typical)	2,700 ANSI Lumens
Contrast Ratio	800:1
Lamp Life and brand	Estimated at 4000/3000 Hours (Eco/Std) 230W NSH USHIO
Throw Ratio	70" @ 2.0m
Projection Distance	1.4~12.7m
Image Size (Diagonal)	40'~300'
Aspect Ratio	4:3 Native, 16:9 Compatible
Remote Control	IR Remote
Audio	Mono 7-Watt Speaker
Displayable Colors	1.07 Billion
Offset	115%
Uniformity	85%
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
Video Compatibility	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)
Projection Lens I/O	1.2x Manual Zoom and Focus
Connectors	2*VGA-In, VGA-Out, S-Video, Component Video, Audio- Out, RCA (L/R) Audio-Input, RS-232, RJ45
Security	Anti-theft Bar, Kensington® Lock Port and Keypad Lock
Projection Method	Front, Rear, Ceiling Mount, Table Top
Weight	3.30kg
Dimensions (W x H x D)	340 x 240 x 90 mm
Noise Level (STD/Bright)	29dB/34dB
Keystone Correction	±30° Vertical 15~100
Horizontal Scan Rate	KHz
Vertical Refresh Rate	50~100 Hz 0°C to
Operating Temperature	40°C
Power Supply	280W/100 V, 240V @ 50-60Hz
Standard Accessories	Power Cord, VGA Cable, Remote Control, Batteries, Carrying Case, Lens Cover, Owner's Manual, Quick Start Card and Warranty Card