LG Executive, powered by LifeSize[®]



HD Video Communications and Integrated HD Display - All in One Smart, Simple and Streamlined System

The integrated HD video communications solution designed to streamline your business.

LG Executive, powered by LifeSize[®], is the ideal combination of an HD video communications solution and the functionality of a HD display, all in one sleek form factor. This jointly developed offering from LG and LifeSize combines HD quality performance, affordability and interoperability to maximize the return on the customer's video communications investment.

The Smart Choice for Highest Quality of Experience

The solution supports 720p30 HD video calling and is a natural extension of the HD quality customers have come to expect from LifeSize. The device is also broadly interoperable with video conferencing endpoints and IP/PBX installations - enabling executives, remote office employees and teleworkers to connect face-to-face with anyone, anywhere.

The Simple Integrated Solution with Easy Set Up

Users can enjoy a high definition, immersive experience without worrying about set up and space required for a separate camera, video endpoint and display. Deployment is simple and takes only minutes, while the sleek 24" display fits easily on an office desk or in a small workspace.

Streamlined Business Activities and Communications

This integrated system combines HD video, camera, wideband audio, all within an HD resolution display. Business users never have to leave the comfort of their office chair to host or participate in a HD video call and can seamlessly switch back to PC use after their call is complete. Business is streamlined and users become more productive.

LG Executive, powered by LifeSize® Simple. Smart. Streamlined.



Key Features

HD Video Communications	Point-to-point HD video calls at 720p30 HD resolution
High Definition Display	Fully integrated HD video and wideband audio system in a 24" display with 1920 x 1080 HD resolution
Interoperability	Broad interoperability with VTC endpoints, IP / PBX installations and Skype™ (audio)
Easy Set Up for Quick Mainstream Deployment	2 wires to set up system: power and Ethernet
Intuitive Graphical Interface	Easy switching between HD video conferencing, and PC monitor functionality
Compact Form Factor	Integrated 720p camera, microphone array and premium speakers

Product Specifications

System Components

Fully integrated display, camera, microphone, speakers, and codec Cables

Display

24" LCD Monitor 1920 x 1080 resolution, 16:9 aspect ratio Contrast Ratio: 50,000:1 Viewing Angle: 170°/160° Response Time: 2ms (Typical) Brightness: 310 cd/m2 Auto resolution Anti-Glare surface treatment 16.7M colors

Communications

H.323, SIP, Skype™ (audio) 128Kbps – 2.0 Mbps

High Definition 720p Camera

Fixed focus with range from 241MM (9.5") to infinity

Video Specifications / Video Resolutions

Maximum resolutions widescreen 16:9 aspect ratio All resolutions progressive scanning All resolutions at 30 frames per second 192 Kbps (432 x 240 pixels) Widescreen FCIF 384 Kbps (720 x 400 pixels) Cable TV 512 Kbps (800 x 488 pixels) DVD Resolution 768 Kbps (1024 x 576 pixels) 2x DVD Resolution 1.1 Mbps or higher (1280 x 720 pixels) High Definition Actual resolution depends on capability of remote end and is impacted by the quality of the communications channel

Video Standards

H.264, H.263, H.261 and H.239 (receive) compliant

Video Formats

High Definition, 16:9 aspect ratio

Video Inputs (2 Inputs)

1 x HDMI 1 x VGA

High Definition Audio Input

Dual Omni-directional, beam forming microphones 100Hz up to 16 kHz

Audio Features

High Definition audio Built in ringer GIPS NetEQ packet loss concealment Full duplex for natural conversations Echo cancellation for echo-free calls Automatic noise reduction Automatic gain control

Audio Standards

G.711, G.722, G.722.1 (Polycom© Siren14™), G.728, G.729, MPEG-4 - AAC-LC

Audio Input

1 x Microphone In (3.5mm)

Audio Output

1 x Line Out/Headset (L+R) (3.5mm)

Other Supported Standards

H.221, H.224, H.225, H.231, H.241, H.245, H.281, BONDING (ISO13871) via LifeSize Networker, RFC 3261, RFC 3264, RFC 2190, RFC 3407, RFC 2833

Network Interfaces

Integrated 2-port Ethernet switch 1 x RJ-45 Network LAN 1 x RJ-45 for PC connectivity

User Interface & Features

Context sensitive user interface Graphical User Interface Call Manager Multiple languages supported Do Not Disturb mode

LG Executive, powered by LifeSize[®]

Security

Admin and User-level password SNMP security alerts Ability to disable HTTP, SSH and Telnet services H.235 (AES) encryption support including strict compliance TLS/SRTP support IEEE 802.1x support Kensington Security Slot™

Intelligent Networking Features

Adaptive Motion Control (AMC) NAT/Firewall Traversal (H.460/SIP) IPv4 and IPv6 support Auto bandwidth detection

Directory and Address Book

Up to 1000 local directory entries Save, Lock, Remove Redial List features Missed call notification Auto-Discovery directory lookup (patent pending) LDAP support/H.350 compliant Meetings Skype™ Contacts support

System Management

SNMP Backup and Restore capability

Power

AC Voltage 100-240V, 50-60 Hz

Environmental Data

Operating temperature: • 0°C (32°F) to 35°C (95°F) Operating humidity: • 15% to 85%, non-condensing Storage temperature: • -20°C (-4°F) to 60°C (140°F) Storage humidity: • 10% to 90%, non-condensing

Dimensions

- Width: 23.4" (594mm)
- Depth: 2.8" (71mm)
- Height: 20.3" (515mm)

For additional information: www.lifesize.com/support

Information contained in this document is preliminary and subject to change without notice. LifeSize[®] is the registered trademark or trademark of LifeSize Communications Inc. All other trademarks are the property of their respective owners. For patents covering LifeSize[®] products, refer to http://www.lifesize.com/support/legal. ©Copyright 2010. All rights reserved.



LifeSize®

LifeSize Communications: 901 S. Mopac Expressway Building 3, Suite 300 Austin, Texas 78746 USA Phone: +1 512 347 9300 Fax: +1 512 347 9301 Email: info@lifesize.com www.lifesize.com EMEA: LifeSize Communications Toll-Free Europe 008000 999 09 799 APAC: LifeSize Communications Hong Kong Phone: +852 3189 7061